

# HT-VIEW

## Decoder HS-16



## Specification

|                     |   |
|---------------------|---|
| Video compression   | H.265+/H.265, H.264+/H.264, M-JPEG  |
| Input               | VGA, DVI-I  |
| Input Resolution    | VGA, DVI-I: 1080p   |
| Output              | HDMI x 16, BNC x 8  |
| Output Resolution   | HDMI: 4K: 3840 x 2160 @30Hz,<br>1080p: 1920 x 1080 @50/60Hz   |
| Decoding Capability | 1080p@30fps/3Mbps:128-ch<br>3mp@30fps:80-ch<br>5mp@30fps:48-ch<br>8mp@30fps:32-ch<br>12mp@20fps:16-ch   |
| Decoding Resolution | Up to 24mp  |
| Decoding Channel    | 128-ch  |
| Network Interface   | RJ45 Interface x 2, 10/100/1000 Mbps<br>Optic Interface x 2, 100 base-FX/1000 base-X<br>An RJ45 Interface and an optic interface form a combo |
| Serial Interface    | RS-232 x 1, RS-485 x 1  |
| Audio Output        | 16 ( DB15 x 2)  |
| Two-way Audio Out   | 1 (3.5mm connector, 2.0   |
| Alarm In            | 8   |
| Two-way Audio In    | 1 (3.5mm connector, 2.0   |
| Alarm Out           | 8   |
| Power Supply        | 100 to 240 VAC  |