



Specification & Features

- Add cameras in batches by importing an Excel file from a USB drive
- PTZ control, setting and calling preset, patrol and pattern
- POE power supply , Wired and Wi-Fi network connection
- DVI and HDMI output to monitor
- Control of MVC and decoders for video decoding and output on video wall
- Access to products including DVR, DVS, NVR, network camera, speed dome, etc.
- Detachable design of the touchscreen and joystick
- Wired and Wi-Fi network connection
- Capable of decoding 2-ch at 1080P decoding; up to 16-division window display
- Live view on touch panel
- Support upgrade and configuration files import/export by USB flash disk
- Support recording and picture files in USB flash disk or uploading to FTP server
- Plug & Play

Operating System	Android 6.0
TFT LCD Screen	10.1" TFT LCD Touchscreen Resolution: 1280 x 800
Joy Stick	4-axis joystick
Local Decoding	Local live view at 1080p/720p/HDI/BCIF/CIF/QCIF Resolution and up to 16-division window display
Two-way Audio Input	1-ch, 3.5mm connector (2.0Vp-p,>1k Ω)
Audio Output	1-ch 3.5mm connector (2.0Vp-p, 600 Ω)
Network Interface	10/100/1000
Wi-Fi	Supported
USB Interface	2.0 x 2
Video Interface	HDMI, DVI
Power Supply	12V DC/PoE
Consumption	$\leq 15W$
Working Temperature	-10 °C - + 55 °C
Working Humidity	10% - 90%