



H-2MP

2MP Bullet Network Camera



Technical Specification

Camera	
Image Sensor	1/2.8" 2Megapixel Progressive Scan CMOS
Max. Resolution	1920 (H) × 1080 (V)
ROM	128 MB
RAM	128 MB
Min. Illumination	Color: 0.005 Lux , B/W: 0 Lux with IR
Wide Dynamic Range	120 dB
Day & Night	IR Cut Filter
Lens	
Lens Type	Motorized lens, 2.7 to 13.5 mm
Lens Mount	Ø 14
Iris Type	Fixed
Aperture	F1.6
Video	
Video Frame Rate	Main Streaming: 1920 x 1080 Sub Streaming: 704 x 576(1fps-25fps), 704 x 480(1fps-30fps)
Smart Codec	Smart H.265+/H.264+
Video Compression	H.265/H.264, MJPEG Sub-stream: H.265/H.264/MJPEG
Stream Capability	2 Streams
Resolution	1080p (1920 x 1080); 1.3M (1280 x 960); 720p(1280 x 720);
Day/Night	Auto(ICR)/Color/B/W
WDR	120 dB
Gain Control	Auto/Manual
Motion Detection	On/Off (4 areas, rectangular)



Network	
Protocols	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PoE, NTP, UPnP™, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Bonjour
SDK and API	Yes
Network	RJ-45 (10/100 Base – T)
Interoperability	ONVIF
Storage	FTP; Micro SD Card (Support max. 256G) NAS; SFTP
Certification	
Certification	CE-LVD : EN62368-1 CE-EMC : Electromagnetic Compatibility Directive2014/30/EU FCC: 47 CFR FCC Part 15, Subpart B UL/CUL: UL60950-1 CAN/CSA C2.2
Power	
Power Supply	12V DC/PoE (IEEE802.3af)
Power Consumption	< 9.6W
Environment	
Operating Condition	-30 °C to +60 °C (-22 °F to +140 °F)/less than ≤ 95% RH
Storage Temperature	-40 °C to +60 °C (-40°F to +140 °F)
Protection	IP67; IK10 (Optional)
Structure	
Casing	Metal
Dimensions	244.1 x Φ90.4
Gross Weight	1.15 kg